

## STB-UMT-S265-MINI



STB-UMT-S265-mini is set-top box (STB, receiver, television decoder) which works in DVB-S and DVB-S2 standards and supports MPEG-2/MPEG-4/H.264/HEVC/H.265 codecs, also has CA smart card slot.

STB-UMT-S265-mini :

- Fully DVB-S/DVB-S2/MPEG-2/MPEG-4/H.264/HEVC/H.265 compliant
- CVBS/RGB/YPbPr/HDMI/Scart output supported,USB 2.0 port PVR, multi-media player
- SCPC & MCPC receivable from C/Ku band satellites
- DiSEqC 1.0/1.1/1.2/1.3(USALS) supported
- Universal LNB, NIT search support
- Electronic program guide (EPG) , VBI Teletext,Supports up to 64 satellites
- Up to 2,500 transponders, Frequency range: 950 ... 2150 MHz
- Auto/Manual Program search, Multi-language supported
- USB 2.0 for PVR, Timeshift, Software upgrade, Multimeida Playback,OTA software upgrade
- Transmission mode: LDPC/BCH (DVB-S2) 8PSK/QPSK, DVB-S QPSK
- Support up to 5000 channels
- Support up full HD 1080P,HDMI 1.3
- Support Multi CAS
- Support multi-TS stream

### DVB-S2 Specification

#### Tuner

InputFrequency Range	950MHz to 2150MHz
Input Impedance	75Ohms unbalanced
Signal Input Level	-65 ~ -25dBm
Symbol Rate	2-45Mbps
LNB Power	13/18V,Max 350mA
	47-862 MHz
<b>Demodulation</b>	
Demodulator	QPSK/8PSK
FEC Modes Rate	1/2,2/3,3/4,5/6,7/8,8/9,9/10
<b>System Resources</b>	
SDRAM memory	1Gbit DDR3
FLASH memory	64Mbit FLASH
<b>Video Decoder</b>	
Standard	ISO/IEC 13818-2 and ISO/IEC 14496-10
Transport stream	ISO/IEC 13818-1
Video decoding	HEVC/H.265,MPEG-4 H.264/AVC SD/HD,MPEG-2 SD/HD (MP@ML and MP@HL), JPEG,BMP,PNG, Motion JPEG AVI, VOB, MOV, MKV
Video Resolution	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Aspect ratio	4:3, 16:9 Auto

Audio Decoder	
Standard	MPEG-1 Layer I & II, MPEG-2 Layer II, AAC, MP3, HE-AAC,AC-3(optional), E-AC-3(optional)
Sample rate	32, 44.1, 48
Subtitles & Teletext	
Subtitle	DVB Subtitle
Rear Panel	
HDMI	HDMI version 1.3
LNB Input	IEC169-2 Female
USB	2
RS232	1
CVBS & Audio R/L	RCA(1 ports)
IR Port	IR External LED Display
Accessories	
Remote control unit	IR 38kHz NEC
User Manual	1 in English
RCA cable	1(Optional)
HDMI Cable	1(Optional)
Power	
DC INPUT	12V/1.5A(Optional)
Power consumption	Max 18W

Physical	
Operating Temperature	0 ~ 45 °C
<p>Remarks:</p> <ol style="list-style-type: none"><li>1. Delivery term: FOB Shenzhen</li><li>2. Payment term: 30% deposit,balance T/T before shipment</li><li>3. Lead time: 30 days after deposit</li><li>4. One year warranty starts from ETA</li></ol>	

*Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.*

**Note!** *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*